



**Data Sheet**  
**Biooil type: PRIMEOL**

<b>Parameter</b>	<b>Value</b>	<b>Unit</b>	<b>Method</b>
Heat of Comb. Gross	38,9	MJ/kg	ASTM D 240
Heat of Comb. Net	36,4	MJ/kg	ASTM D 240
Flash Point	> 160	C	ASTM D93/A
Ash	< 0,05	% mass	ASTM D 482
Water KF	< 0,8	% mass	ASTM D 1744
Free Fatty Acids	< 20	% mass	DGF C-III 4
Sulfur	< 0,07	% mass	ASTM D 4294
Carbon	75,8	% mass	ASTM D 5291
Hydrogen	11,4	% mass	ASTM D 5291
Nitrogen	< 0,1	% mass	ASTM D 5291
Pour Point	< 15	C	ASTM D 97
Density	0,89	Kg/liter	ASTM D 792
Viscosity (60 C)	20-30	mm <sup>2</sup> /s	ASTM D 445

**Øko-Oil Aps**  
[info@eko-oil.dk](mailto:info@eko-oil.dk)  
[www.eko-oil.dk](http://www.eko-oil.dk)

Hovedkontor:  
Telemarken 7  
5600 Faaborg

Tankterminal:  
Mørkebjergvej 13  
5600 Faaborg